

Seascope: The *Seascope* series introduces high definition designs with the latest Engineered Vinyl technology and durable surface treatments. With looks mirroring the majesty and beauty of ocean fronts and with the thrills of adventure, this floor will truly shine in your home.

PRODUCT INFORMATION (Plank Specifications - Residential)

Construction Type:	High Pressure Core (HPC) Watershield HPC
Grade:	Rustic (includes simulated knots and mineral streaks)
Color Choice:	Refer to Johnson's product sheet
Wear-Layer Thickness:	20 mil (.5 mm)
Vinyl Thickness:	2.0 mm
Overall Thickness:	7.5 mm
Core Material:	4.0 mm Watershield Core
Width:	9" (nominal)
Length:	60" (nominal)
Dimensional Stability:	≤0.25% / lin. Ft. / (305mm) avg. max
Squareness ^A :	Maximum 0.010 in. (0.25mm)
Click System:	Valinge Triple lock click
Underlayment:	1.0 mm Cork
Style:	Embossed in Register
Finish:	Polyurethane
Luster:	Matte
Resistance to light:	ΔE < 8 ave., max (Protect from direct sun light)
Resistance to heat:	ΔE < 8 ave., max (Floor temperature must not exceed 85 degrees F).
Color Tone/Variation:	Moderate

INSTALLATION: Floating

Subfloor: Refer to Guidelines

PACKAGING:

SQ/FT Per Carton:	18.04
Cartons Per Pallet:	68
PCS Per Carton:	5
Pounds Per Carton:	33

PERFORMANCE:

	TEST METHOD	RESULTS
IIC / STC / ΔIIC 6" slab only Unless otherwise indicated (** indicates ceiling assy.)	ASTM E90, ASTM E492, ASTM E2179	58 / 51 / 23**
ASTM E648 Fire Resistance:		Class 1
ASTM E662 Smoke Generation:		Passes

WARRANTY PERIODS FOR JOHNSON HARDWOOD VINYL PRODUCTS:

- ❖ Limited Lifetime Structural Warranty
- ❖ Limited Lifetime Residential Wear Warranty
- ❖ Limited Lifetime Waterproof Warranty
- ❖ Limited Lifetime Petproof Warranty

❖ **Limited 15-Year Commercial Wear Warranty**

PRODUCT INFORMATION (Tile Specifications - Residential)

Construction Type:	High Pressure Core (HPC) Engineered LVT
Grade:	N/A
Color Choice:	Refer to Johnson's product sheet
Wear-Layer Thickness:	20 mil (.5 mm)
Overall Thickness:	5.0 mm
Core Material	4.0 mm
Width:	18" (nominal)
Length:	36" (nominal)
Dimensional Stability:	TBT
Squareness ^A :	TBT
Click System:	Valinge 5G
Style:	Polished concrete, slate and stone
Finish:	Polyurethane
Luster:	Matte
Resistance to light:	Protect from direct sun light
Resistance to heat:	Floor temperature must not exceed 80 degrees
Color Tone/Variation:	Minimal

INSTALLATION: Floating

Subfloor: Wood, concrete

PACKAGING:

SQ/FT Per Carton:	17.61
Cartons Per Pallet:	54
PCS Per Carton:	4
Pounds Per Carton:	34

PERFORMANCE:	TEST METHOD	RESULTS
IIC / STC / ΔIIC 6" slab only Unless otherwise indicated (* indicates ceiling assy.)	TBT TBT	
ASTM E648 Fire Resistance:		TBT
ASTM E662 Smoke Generation:		TBT

WARRANTY PERIODS FOR JOHNSON HARDWOOD VINYL PRODUCTS:

- ❖ **Limited Lifetime Structural Warranty**
- ❖ **Limited Lifetime Residential Wear Warranty**
- ❖ **Limited Lifetime Waterproof Warranty**
- ❖ **Limited Lifetime Petproof Warranty**
- ❖ **Limited 15-Year Commercial Wear Warranty**