

Rowlock Plus wood panels have been constructed from all natural wood materials. Each raw wood piece has been hand-sanded and hand-stained to preserve the undressed elegance of the wood species. Plantation pine backer not only adds to the sustainability but also the durability of each panel. Undulations in the profile display rough-hewn wood characteristics.

PRODUCT INFORMATION

Construction:	Engineered
Thickness (Linear):	Nominal 3/8" to 1/2"
Thickness (Square):	Nominal 1/2" to 1"
Width (Linear):	9.5"
Width (Square):	8.5"
Length (Linear):	53.0"
Length (Square):	50.5"
Style:	Rustic / Elegant
Finish:	Urethane
Luster:	Satin
Backer:	Pine

INSTALLATION: Brad Nail, and Glue

PACKAGING

SQ/FT Per Carton (Linear):	18.8
SQ/FT Per Carton (Square):	15.5
Cartons Per Pallet:	40 (Linear) / 35 (Square)
Pounds Per Carton:	24/27
PCS Per Carton:	6 (linear) / 6 (Square)

PERFORMANCE

Fire Test Data – Flame Spread/Smoke

TEST METHOD

ASTM E 84-16

* Hickory, Oak, and Acacia (Results-B Rating)

* American Walnut (Results-C Rating)

WARRANTY

35-YEAR LIMITED STRUCTURAL AND FINISH WARRANTY (see warranty for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES.