

Manufacturer of Unique High Quality Floors

Ale House

Technical Specifications

AleHouse: The Alehouse series puts emphasis on the details to create a totally unique flooring experience. A multi-layer, hand-staining process has been used to create an inner glow effect that darkens towards the timeworn plank edges. Due to the natural glow, the Alehouse series has high color variation. Meaning the color hues will span a range from low too high for added brilliance. Vintage, long-length planks measure up to seven-feet long for a more coalescent floor. Our exclusive vintage surface treatment finish adds even more character for the look of a reclaimed, custom hardwood floor.

PRODUCT INFORMATION

Construction: Engineered prefinished hardwood flooring with tongue and grooves

Species: Maple and European White Oak

Grade: Rustic (includes knots, splits, mineral streaks and filler)

Color Choice: Refer to Johnson's product sheet Wear-Layer Thickness: Nominal 2.0 mm (Sliced cut)

Overall Thickness: Nominal ½" (12.7 mm)

Core Material (Species) Varies between Birch, Poplar and Eucalyptus

Width: 7-½" (190.5 mm)

Length: Most boards come in 7' lengths

Style: Hand-scraped, pillowed edges, with a wire brushed surface
Finish: Aluminum oxide particulates suspended in UV cured polyurethane

Luster: Semi-Gloss

UV Sensitivity: Stains/Dyes can/will fade when exposed to UV light. Wood

(Depending on the species) can/will lighten and/or darken when

exposed to UV Light.

Color Tone/Variation: Moderate to High

INSTALLATION: Staple, Glue or Float (above, on, or below grade)

Subfloor: Refer to installation guidelines

PACKAGING

SQ/FT Per Carton: 26
Cartons Per Pallet: 55
Pounds Per Carton: 41

PERFORMANCE TEST METHOD RESULTS

Taber Abrasion: D4060 400 to 500 revolutions

Species Hardness Based on NWFA Janka: ASTM-D-143 European White Oak (1360) Maple (1450)

Formaldehyde: CARB Phase 2 Compliant

WARRANTY

35-YEAR LIMITED STRUCTURAL WARRANTY AND FINISH WARRANTY (see warranty @ johnsonhardwood.com for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES, OR IN FULLY FUNCTIONAL BATH ROOMS, WHICH CONTAIN BATH TUBS AND/OR SHOWERS.