

**Reservoir:** Johnson *Reservoir Series* with the advantages of both wood and luxury vinyl, Johnson Hardwood proudly introduces its newest in innovation and technology, a waterproof wood floor. The Reservoir Series uses a natural hardwood wear layer providing distinct details such as open gains and no repetition in patterns for each plank. Resistance to moisture, pet stains, and routine water spills can be achieved from top to bottom up within a 72-hour period with our patented WaterShield Ridgid Core technology. FloorScore certified, formaldehyde and phthalate free, and pre-attached underlayment makes our Reservoir Series the ideal solution for families who are looking for a real wood floor without the worries.

### PRODUCT INFORMATION (Plank Specifications – Residential and Light Commercial, Interiors Only)

#### NOTE: TEST DATA DOCUMENTATION AVAILABLE UPON REQUEST

<b>Construction Type:</b>	<b>SPC Component, Engineered Wood / Vinyl Floor, Marine Grade Adhesive</b>
Grade:	Smooth surface including micro bevel
Color and Species Choice:	Refer to Johnson's product sheet
Wear-Layer Thickness:	0.4 mm
Overall Thickness:	5.9 mm
Underlayment:	1.5 mm Sound Control Attached Underlayment
Core Material	WaterShield Core
Width:	6 1/2 "(nominal)
Length:	48" (nominal)
Click System:	Valinge 2G Click
Finish:	Proprietary Finish Technology Using AL/OX Particles for Greater Wear Resistance
Luster:	Semi-Gloss
Color Tone/Variation:	Moderate

**INSTALLATION:** Floating

**Subfloor:** Refer to Guidelines

#### PACKAGING:

SQ/FT Per Carton:	12.81
Cartons Per Pallet:	72
PCS Per Carton:	Random
Pounds Per Carton:	30

#### PERFORMANCE:

Concrete Slab w/Drop Ceiling:
Concrete Slab Only:
Flame Spread Index:
Smoke Development Index:
Critical Radiant Flux:
Phthalate Determination:
Taber Abrasion:
Surface Friction Properties:
Dynamic Rolling Load:
Static Load Limit:

#### TEST METHOD

ASTM E90, and E492
ASTM E90, E493, E2179
ASTM E84-16
ASTM E84-16
ASTM E648-17A
ASTM D7823
ANSI/NALFA LF-01-2011
ASTM E303-93
ASTM F2753-10
ASTM F970-17

#### RESULTS

STC: 62, IIC: 64
STC: 52, IIC: 51, Delta IIC: 21
85
195
0.58 W/cm <sup>2</sup>
0.97 PPM
370 rev
26 BPN
No cracking or surface damage
Average residual indentation 0.0238"

**WARRANTY PERIODS FOR JOHNSON HARDWOOD VINYL PRODUCTS:**

- ❖ **Limited Lifetime Structural Warranty**
- ❖ **Limited 35-Year Residential Finish Warranty**
- ❖ **Limited 72-Hour Topical Moisture Warranty**
- ❖ **Limited Lifetime Petproof Warranty**
- ❖ **Limited 5-Year Light Commercial Warranty**