Johnson.Hardwood

Manufacturer of Unique High Quality Floors

Oak Grove

Technical Specifications

Oak Grove: Step into a world of timeless beauty with Oak Grove – the new engineered wood flooring that captures the essence of European oak. With its random length, wire brushed texture, and low gloss finish, Oak Grove adds a touch of rustic elegance to any space. Crafted to perfection with UV cured aluminum oxide, this ½" thick flooring promises durability and longevity. Choose from a stunning collection of 6 colors in prime abcd grade or 4 colors in prime select or ab grade. Transform your home with the warmth and character of Oak Grove and create your very own love story with every step.

PRODUCT INFORMATION

Construction: Engineered prefinished hardwood flooring with tongue and grooves

Species: European White Oak

Grades: Rustic ABCD grade (includes knots, filled knots and light wire brushing). Prime

select AB grade (may include small knots, along with light wire brushing).

Color Choices: Refer to Johnson's product info sheet.

Wear-Layer Thickness: Rustic grade – nominal 1.2mm veneer. Prime grade – nominal 1.8mm veneer.

Veneer Cutting Method: Slice cut.

Overall Thickness: Nominal 1/2"

Core Material (Species): Varies between Birch, Poplar and Eucalyptus

Width: Nominal 7 1/2"

Length: Nominal Random 11" to 75" for ABCD Grade and 20" to 75" for AB Grade

Style: Surface texture, light wire brushed along with beveled edges
Finish: Aluminum oxide particulates suspended in UV cured polyurethane

Luster: Low

UV Sensitivity: Stains/Dyes can/will fade when exposed to UV light. Wood

(Depending on the species) can/will lighten and/or darken when

exposed to UV Light.

Color Tone/Variation: High

Country of Origin: Vietnam

Warranty: 35 Year Limited Residential (Non-Transferable)

INSTALLATION: Staple, Glue or Float (above, on, or below grade. Refer to installation guidelines)

Subfloor: Refer to installation guidelines

PACKAGING (RUSTIC GRADE)

SQ/FT Per Carton: 23.4
Cartons Per Pallet: 55
SQ/FT Per Pallet: 1,287

Pounds Per Carton: Approximately 43 lbs.

PACKAGING (PRIMIUM GRADE)

SQ/FT Per Carton: 31.09
Cartons Per Pallet: 36
SQ/FT Per Pallet: 1,119.24

Pounds Per Carton: Approximately 55 lbs.

PERFORMANCE TEST METHOD RESULTS

Species Hardness Based on Janka: ASTM-D-143 European White Oak

(1020)

Formaldehyde: (CARB Phase 2 Compliant)

TSCA Title VI: (Compliant)

WARRANTY

35-YEAR LIMITED STRUCTURAL AND FINISH WARRANTY (see warranty for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES, OR IN FULLY FUNCTIONAL BATHROOMS, WHICH CONTAIN BATHTUBS AND/OR SHOWERS.

825 Sentous Ave., Industry, CA 91748 • Tel: 800-910-3047 • Fax: 888-507-0686 • <u>www.JohnsonHardwood.com</u> (5-30-24)