

Countryside Oak: Introducing Johnson Hardwood’s Countryside Oak: engineered hardwood flooring crafted from premium European Oak. This budget-friendly flooring offers both elegance and resilience with a generous 7-1/2” width and sturdy 3/8” thickness. Each plank features a 1.0 mm veneer, enhanced by a light wire-brushed finish and a UV-cured aluminum oxide coating for superior durability. With 10 stunning SKUs, such as Tortilla, Driftwood, and Pebble, the Countryside Oak collection captures a palette inspired by the rich tones and textures of nature. Elevate your home with the timeless beauty and affordability of Countryside Oak, where every detail reflects a heritage of quality and rustic charm. THIS PRODUCT IS ONLY AVAILABLE IN SELECT MARKETS. PLEASE CONTACT YOUR SALES REPRESENTATIVE FOR DETAILS.

PRODUCT INFORMATION

Construction:	Engineered prefinished hardwood flooring with tongue and grooves
Species:	European Oak
Grade:	Semi Rustic A B C D grade (includes knots, filled knots and light wire brushing)
Color Choice:	Refer to Johnson’s product info sheet
Wear-Layer Thickness:	Nominal 1.0 mm (Slice cut)
Overall Thickness:	Nominal 3/8” (9.525 mm)
Core Material (Species)	Varies between Birch, Poplar and Eucalyptus
Width:	7-1/2” (190.5 mm)
Length:	Random 16.0” (406.4 mm) to 67” (1701.8 mm)
Style:	Surface texture, light wire brush along with beveled edges
Finish:	Aluminum oxide particulates suspended in UV cured polyurethane
Luster:	Matte
UV Sensitivity:	Stains/Dyes can/will fade when exposed to UV light. Wood (Depending on the species) can/will lighten and/or darken when exposed to UV Light.
Color Tone/Variation:	High

INSTALLATION: Staple or Glue (above, on or below grade. Refer to installation guidelines)

Subfloor: Refer to installation guidelines

PACKAGING

SQ/FT Per Carton:	43
Cartons Per Pallet:	45
Pounds Per Carton:	55
SQ/FT Per Pallet:	1, 935

PERFORMANCE

Species Hardness Based on Janka: (1020)
Formaldehyde: (CARB Phase 2 Compliant)
TSCA Title VI: (Compliant)

TEST METHOD

ASTM-D-143

RESULTS

European White Oak

WARRANTY

35-YEAR LIMITED STRUCTURAL AND FINISH WARRANTY (see warranty for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES, OR IN FULLY FUNCTIONAL BATHROOMS, WHICH CONTAIN BATHTUBS AND/OR SHOWERS.