Johnson.Hardwood

Manufacturer of Unique High Quality Floors

Texas Timber

Technical Specifications

Texas Timber: Crafter from European oak with a light wire brushed finish. Each plank features a 1.2mm sliced veneer and a UV-cured aluminum oxide finish, showcasing the resilience and strength of the Lone Star State. Bringing a touch of rustic elegance to your home at a friendly price point, Texas Timber combines refined style with a thickness of 3/8" and a width of 7-1/2". The series features 10 colors representing the hues and tones of Texas, with names like Alabaster, Sand, Tawny, and Carob – to name a few. Experience the timeless allure of Texas with every step.

PRODUCT INFORMATION

Construction: Engineered prefinished hardwood flooring with tongue and grooves

Species: European Oak

Grade: Semi Rustic A B C D grade (includes knots, filled knots and light wire brushing)

Color Choice: Refer to Johnson's product info sheet

Wear-Layer Thickness: Nominal 1.2 mm (Slice cut)
Overall Thickness: Nominal 3/8" (9.525 mm)

Core Material (Species) Varies between Birch, Poplar and Eucalyptus

Width: 7-1/2" (190.5 mm)

Length: Random 16" (406.4 mm) to 75" (1905.0 mm)

Style: Surface texture, light wire brush along with beveled edges
Finish: Aluminum oxide particulates suspended in UV cured polyurethane

Luster: Matte

UV Sensitivity: Stains/Dyes can/will fade when exposed to UV light. Wood

(Depending on the species) can/will lighten and/or darken when

exposed to UV Light.

Color Tone/Variation: High

INSTALLATION: Staple or Glue (above, on or below grade. Refer to installation guidelines)

Subfloor: Refer to installation guidelines

PACKAGING

SQ/FT Per Carton:38.9Cartons Per Pallet:45Pounds Per Carton:52SQ/FT Per Pallet:1, 750.5

PERFORMANCE TEST METHOD RESULTS

Species Hardness Based on Janka: ASTM-D-143 European White Oak

(1020)

Formaldehyde: (CARB Phase 2 Compliant)

TSCA Title VI: (Compliant)

WARRANTY

35-YEAR LIMITED STRUCTURAL AND FINISH WARRANTY (see warranty for further information).

WARNING: NOT TO BE INSTALLED NEAR OPEN FLAMES OR EXCESSIVE HEAT SOURCES, OR IN FULLY FUNCTIONAL BATHROOMS, WHICH CONTAIN BATHTUBS AND/OR SHOWERS.